



OBEIKAN TECHNICAL FABRICS CO. LTD.

PO Box 1087, Riyadh 11431 Kingdom of Saudi Arabia

Tel: +966 1 2653533 Fax: +966 1 2653438

Website: www.obeflex.com

Email: otf@obeikan.com.sa

TECHNICAL DATA SHEET

Product: LAMBADA FP65

Application:

- Outdoor - Banners, posters
- Indoor - Panels, banners, decorations and displays

PROPERTIES	TEST METHOD	METRIC	ENGLISH
Support Cloth	(DIN 60001)	Polyester	Polyester
Ends/Picks	(DIN EN 1049-2)	7 x 4.7 per cm	18 x 12 per inch
Yarn (dtex)	(DIN EN ISO 2060)	330 x 550	
Weave	(DIN ISO 9354)	WKWI	WKWI
Type of Coating		PVC laminated on both sides	PVC laminated on both sides
Total weight	(DIN EN ISO 2286-2)	650 ±20 g/m ²	19.14 oz./sq.yd.
Width	(DIN EN ISO 2286-1)	up to 320 cm	up to 10'6"
Tensile Strength	(DIN 53354)	500/900 N/5cm	57/103 lbs/inch
Tear Resistance	(DIN 53356)	100/100 N	22/22 lbs
Adhesion	(DIN 53357)	>70/90 N/5cm	>8/10 lbs/inch

Features:

- ★ Enhanced printing w/ solvent base ink jet printers
- ★ High-frequency and hot-air weldable
- ★ Available in gloss and matte finish

NOTE: Information listed above is based on our general experience and observation and is given in good faith. OTF will not accept any responsibilities with respects to factors outside our knowledge. Values without tolerance statements are values with a tolerance of ±5%.