



OBEIKAN TECHNICAL FABRICS CO. LTD.

PO Box 1087, Riyadh 11431 Kingdom of Saudi Arabia

Tel: +966 1 2651144 Fax: +966 1 2653438

Website: www.obeflex.com

Email: otf@obeikan.com.sa

TECHNICAL DATA SHEET

Product: CYBERTEX™

Application:

- Indoor - Panels, banners, decorations, flags and displays

PROPERTIES	TEST METHOD	METRIC	ENGLISH
Support Cloth	(DIN 60001)	Polyester	Polyester
Ends/Picks	(DIN EN 1049-2)	26 x 20 per cm	66/51 per inch
Yarn (dtex)	(DIN EN ISO 2060)	300	
Weave	(DIN ISO 9354)	1/1 plain	1/1 plain
Type of Coating		Acrylic coated on both sides	
Total weight	(DIN EN ISO 2286-2)	260 ±5 g/m ²	7.61 oz./sq.yd.
Tensile Strength	(DIN 53354)	1500/1000 N/5cm	137/114 lbs/inch
Tear Resistance	(DIN 53356)	36/34 N	9/9 lbs

Available widths: 4.85m, 4.2m, 3.2m, 2.5m, 2.1m, 1.8m, 1.6m

Features:

- ★ Exclusive surface treatment for consistent image quality and color density
- ★ Compatible for solvent based inkjet printers.
- ★ Light weight material.
- ★ Printable both sides

NOTE: Information listed above is based on our general experience and observation and is given in good faith. OTF will not accept any responsibilities with respects to factors outside our knowledge. Values without tolerance statements are values with a tolerance of ±5%.
