



OBEIKAN TECHNICAL FABRICS CO. LTD.

PO Box 1087, Riyadh 11431 Kingdom of Saudi Arabia

Tel: +966 1 2651144 Fax: +966 1 2653438

Website: www.obeflex.com

Email: otf@obeikan.com.sa

TECHNICAL DATA SHEET

Product: CYBERTEX 310™

Application:

- Indoor - Panels, banners, decorations, flags and displays

| PROPERTIES | TEST METHOD | METRIC | ENGLISH |
|------------------|---------------------|------------------------------|------------------|
| Support Cloth | (DIN 60001) | Polyester | Polyester |
| Ends/Picks | (DIN EN 1049-2) | 26 x 20 per cm | 66/51 per inch |
| Yarn (dtex) | (DIN EN ISO 2060) | 300 | |
| Weave | (DIN ISO 9354) | 1/1 plain | 1/1 plain |
| Type of Coating | | Acrylic coated on both sides | |
| Total weight | (DIN EN ISO 2286-2) | 310 ±5 g/m ² | 9.07 oz./sq.yd. |
| Tensile Strength | (DIN 53354) | 1500/1000 N/5cm | 137/114 lbs/inch |
| Tear Resistance | (DIN 53356) | 36/34 N | 9/9 lbs |

Available widths: 4.85m, 4.2m, 3.2m, 2.5m, 2.1m, 1.8m, 1.6m

Features:

- ★ Exclusive surface treatment for consistent image quality and color density
- ★ Compatible for solvent based inkjet printers.
- ★ Light weight material.
- ★ Printable both sides

NOTE: Information listed above is based on our general experience and observation and is given in good faith. OTF will not accept any responsibilities with respects to factors outside our knowledge. Values without tolerance statements are values with a tolerance of ±5%.
